

MAN TGX 18.440 4X2 BLS

SHV0020126



MAN | TopUsed

Price **15,990 EUR** (net)
19,348 EUR (gross)

Offer Date 30.01.2026

Body type	Tractor unit
1st reg.	01/2012
Power	324kW (441 HP)
Mileage	881357 km
Storage location	Otopeni - MHS Truck Service

BASIC DATA

Brand	MAN
Model serie	TGX
Model variant	TGX TG2
Body type	Tractor unit (Standard)
Colours	white
Driver's cab	XLX
Berths	1 berth

TECHNICAL DATA

Power	324 kW (441 HP)
Fuel	Diesel
Gearbox type	Automatic
Wheel drive	4x2
Suspension	Leaf air suspension
Axles	2 axles

WEIGHTS AND MEASURES

GVW	18,000 kg
Rear overhang	800 mm
Wheel base	3600 mm
Fuel tank	AdBlue: 100 l Fuel tank: 450 l Fuel tank: 760 l
Emission category	Euro5

EQUIPMENT

Safety

- Antilock Braking System ABS
- Anti Slip Regulation ASR
- Electr. Stability Programm ESP
- Immobilizer
- Intarder
- Rear underrun
- Electr. and heated kerb mirror: right
- Electr./heated wide angle mirror

Comfort

- Adjustable steering column
- Electric window lift 2x
- Automatic climate control
- Driver's armrest
- Comfortable driver seat
- Central locking with remote control
- Air-suspended driver seat
- Isolated driver's cab
- DC/AC converter

Interior

- Board computer
- Multifunctional steering wheel
- Digital tachograph
- Carpet floor covering

Light and sight

- Fog lights
- Tinted glass
- Headlight range control
- Cornering light
- Ambient lighting

Audio & communication

- Radio/CD

Assistance systems

- Cruise control
- MAN BrakeMatic
- Hill Hold Control HHC
- Speed limiter

Exterior

- Electr. and heated rear view mirrors
- Low noise
- Rear differential lock
- Fifth wheel
- Spare wheel
- Cab Suspension
- Lifting roof (manual)

Equipment packages

- Aero package
- Efficientline package

Wheels and tyres

- Spare wheel carrier

Others

front springs parabolic 7.5 t, rear air suspension 13 t, hub reduction rear axle Hypoid HY-1350, hypoid axle ratio i 2.85, fuel filter heating, cab insulation NORDIC, wiring for tank truck to ADR, ADR Typ AT, supply kit for semitrailer with lifting axle or moving-off aid, trailer socket 24V (7-7-pin), pick-up plate 40 mm